

OCT 03 2005 P01023-US

AMENDMENTS TO THE CLAIMS

1. (Currently amended). In combination, a container and a dispensing closure secured to said container for discharging the contents thereof,
 - a) said container comprising a container body, a sloping collar sloping inwardly and upwardly from said container body, and a neck extending above said sloping collar,
 - b) a bead encircling said neck of said container,
 - c) a lug formed on said sloping collar and extending radially outwardly and away from said neck,
 - d) said dispensing closure comprising a closure body, a lid, and a hinge for securing said lid to said closure body for pivotal movement relative thereto,
 - e) said dispensing closure further comprising a deck ~~extending horizontally from the closure body~~, an aperture through said deck, and an annular collar surrounding said aperture and depending below said deck,
 - f) interrupted beads defined on the interior of said annular collar so that said annular collar may be snapped over said annular bead to seat the dispensing closure upon the container,
 - g) a stop wall defined on a chord extending across the interior of the closure body of said dispensing closure,
 - h) said stop wall including a pair of ribs separated by a central gap, one end of each rib being joined to the interior of said closure body of said dispensing closure to permit pivotal movement, and
 - i) said stop wall cooperating with said lug to define a home position when said dispensing closure is rotated relative to said container after being seated thereon.

P040 P01023-US

Claims 2-3 (cancelled).

4. (Currently amended). The combination of claim 1 wherein reinforcing stays are employed to strengthen said ribs comprising a pair of raised shoulders positioned on ~~the length of one end~~ the respective ends of the ribs and adjacent to the central gap.

5. (Original). The combination of claim 1 wherein said lug is triangular when viewed in side elevation, the upper end of the lug extending parallel to, but spaced below, said annular bead on said container.

6. (Currently amended). The combination of claim ~~[[5]]~~ 1 wherein a segment is formed at the radially extending outer end of said lug by narrowing a portion of said lug to form the segment.

7. (Original). The combination of claim 6 wherein a triangular insert is removed from each of the opposite sides of said segment, thereby forming a dovetailed shape for said segment.

8. (Currently amended). The combination of claim 7 wherein said dovetailed shape of said lug promotes locking of the closure in the ~~aligned or~~ home position, even when relatively high torques are applied to the dispensing closure.

Claim 9 (cancelled).

10. (Previously presented). The combination of claim 1 wherein a recess is formed in the closure body of said dispensing closure diametrically opposite said hinge, said recess enabling the user to lift said cap and pivot same away from said closure body.

P040 P01023-US

Claims 11-14 (cancelled).

15. (Currently amended). In combination, a container and a dispensing closure secured to said container for discharging the contents thereof,

a) the container comprising a container body, a sloping collar sloping inwardly and upwardly from the container body, and a neck extending above the sloping collar,

b) a lug formed on the sloping collar and extending radially outwardly and away from the neck,

c) the dispensing closure comprising a closure body~~[[.]]~~ having a deck ~~extending horizontally from the closure body~~, an aperture through the deck, and an annular collar surrounding the aperture and depending below the deck,

d) a stop wall defined on a chord extending across the interior of the closure body of said dispensing closure, the stop wall including a pair of ribs separated by a central gap, one end of each rib being joined to the interior of the closure body of the dispensing closure to permit pivotal movement,

e) the stop wall cooperating with the lug to define a home position when the dispensing closure is rotated relative to the container after being seated thereon, and

f) means for securing the dispensing closure to the container.

16. (Currently amended). The combination of claim 15 wherein reinforcing stays are employed to strengthen said ribs comprising a pair of raised shoulders positioned on ~~the length of one end~~ the respective ends of the ribs and adjacent to the central gap.

P040 P01023-US

17. (Previously presented). The combination of claim 15 wherein said lug is triangular when viewed in side elevation, the upper end of the lug extending parallel to, but spaced below, said annular bead on said container.
18. (Currently amended). The combination of claim ~~[[17]]~~ 15 wherein a segment portion is formed at the radially extending outer end of said lug by narrowing a portion of said lug to form the segment.
19. (Previously presented). The combination of claim 18 wherein a triangular insert is removed from each of the opposite sides of said segment portion, thereby forming a dovetailed shape for said segment portion.
20. (Currently amended). The combination of claim 19 wherein said dovetailed shape of said lug promotes locking of the closure in the ~~aligned or~~ home position, even when relatively high torques are applied to the dispensing closure.

Claim 21 (cancelled).

22. (Previously presented). The dispensing closure of claim 15 wherein the means for securing the dispensing closure to the container comprises interrupted beads defined on the interior of the annular collar which cooperate with an annular bead on the neck of the container.
23. (Previously presented). A dispensing closure for a container, comprising:
a closure body~~[[,]]~~ having a deck ~~extending from the closure body~~, an aperture through the deck, and an annular collar surrounding the aperture and depending below the deck;
a stop wall defined on a chord extending across the interior of the closure body of the dispensing closure, the stop wall including a pair of ribs separated by a central gap, one end of

P040 P01023-US

each rib being joined to the interior of the closure body of the dispensing closure to permit pivotal movement; and

means for securing the dispensing closure to the container.

24. (Currently amended). The dispensing closure of claim 23 wherein reinforcing stays are employed to strengthen said ribs comprising a pair of raised shoulders positioned on the length ~~of one end~~ respective ends of the ribs and adjacent to the central gap.

25. (Previously presented). The dispensing closure of claim 23 wherein the means for securing the dispensing closure to the container comprises interrupted beads defined on the interior of the annular collar which cooperate with an annular bead on the neck of the container.